

2017 FANTASY TRUCK PULLERS ASSOCIATION, LTD
OPEN STOCK 4X4 RULES

- 1.** Must be factory production vehicle. Truck engine, body and frame must be of same manufacturer. Must have factory functional front suspension. Engine limit - 480 C.I. limit (5 C.I. leeway).
- 2.** No fiberglass bodies. No fiberglass box sides. Fiberglass hood allowed. Fender cut outs allowed. Flatbeds allowed. (No inner fenders needed).
- 3.** Multiple shocks allowed. Blocked or solid suspension allowed. Traction bars allowed. Maximum wheel base 133".
- 4.** Must have windshield and rear window, glass or Plexiglas. Vehicle may not be stripped beyond safe operating condition- hoods, fenders, and doors.
- 5.** Must have brakes. Must be able to skid 2 tires.
- 6.** Exhaust must exit under chassis. Headers allowed.
- 7.** Engine must be in stock location, or no less than 14" from center of front axle to the front of the bell housing.
- 8.** No aluminum heads or aluminum blocks allowed. After market cast iron heads allowed. Any cast iron head accepting stock valve train components within 3 degrees of stock valve angle.
- 9.** Any camshaft. Single carburetor, Holley Dominator, or dominator based carb. Must be of stock configurations - tunnel rams, pro rams, etc. are not permitted. Any cast aluminum intake. No sheet metal intakes. No blowers or hemi heads allowed. Engines must be naturally aspirated.
- 10.** Any ignition except magneto allowed.
- 11.** After market radiators allowed.
- 12.** Electric fuel pumps allowed.
- 13.** All safety equipment required - loops, scatter shield, rear axle covers, and kill switch. All kill switches must shut off ignition and fuel pump.

14. Weight added to front of vehicle may not exceed 60" from center of front axle. Weight is 6000# and 6200#. Without a weight bracket you can run up to an additional 300#. All weight must be behind factory located front bumper. If your running weight behind the front bumper it must not be visible.

15. Adjustable hitch allowed. Height 26" maximum measured at point of hook. No chain hooks. Hitch height checked with weights on.

16. Hitches must be rigid in all directions. Draw bar to be minimum of 27% of truck wheel base from center of rear axle to point of hook and have a clear hook.

17. Maximum tire size 35x12.50/15 or 16.5" tire. Maximum 10-inch rim inside bead to bead. No duals. Must be DOT approved tire. Cyped tires are allowed. If wheel tread is offset, center line of front tire must run within tread of back tire.

18. No nitrous oxide.

19. Any transmission, any transfer case allowed

20. Kill switch must be located in the rear center of the vehicle (maximum of 6 inches left or right off center, maximum of 24 inches above the point of hook). Must have 2" steel ring.

21. Drive trains of 1 ton or less.

22. Any big rear end allowed. No planetary. No aluminum center sections. No chrome molly rear end housing allowed.

23. Must also follow Fantasy Truck Pullers general rules and guidelines